

PATENT APPLICATION
DOCKET NO. P1543US01

APPLICATION
Of
TECKKHOON LIM, MYINT NGWE AND KOKHOE CHIA
For
UNITED STATES LETTERS PATENT
On
USER DATA WEDGE MEDIA CERTIFICATION IN
A DISC DRIVE DATA HANDLING SYSTEM

Docket P1543US01
Sheets of Drawings: 7

Attorneys
Crowe & Dunlevy
1800 Mid-America Tower
20 N. Broadway
Oklahoma City, Oklahoma 73102-8273
Telephone: (405) 235-7700
Facsimile: (405) 239-6651

**USER DATA WEDGE MEDIA CERTIFICATION IN
A DISC DRIVE DATA HANDLING SYSTEM**

Related Applications

This application claims priority to United States Provisional Application No. 60/286,804 filed April 26, 2001.

Field the Invention

The claimed invention relates generally to the field of data handling systems and more particularly, but not by way of limitation, to a method and apparatus for performing a media certification operation on data wedges on disc recording surfaces in a disc drive to detect and map media errors.

Background

A disc drive is a data handling system used to store digital data. A typical disc drive includes a number of rotatable magnetic recording discs which are axially aligned and mounted to a spindle motor for rotation at a high constant velocity. A corresponding array of read/write heads are supported by a rotary actuator and used to access fixed sized data blocks (sectors) on tracks of the discs to write data to and to read data from the discs.

Digital data to be written to the disc recording surfaces are encoded and serialized to provide a sequence of time-varying write currents to the heads. The write currents induce a corresponding sequence of magnetic flux transitions (reversals) along the tracks. The data are subsequently read by transducing the magnetic flux transitions into pulses of an analog readback signal, which is subjected to decoding techniques to recover the originally written digital data. Disc drives of the present generation typically employ sampled amplitude read channels with discrete time sequence detection.

It is common to perform media certification tests to scan the disc surfaces for media defects during disc drive assembly operations. Broadly speaking, media

defects are regions in the magnetic medium of the disc surfaces where data cannot be reliably written and retrieved. A number of factors can induce media defects including minute pinholes, asperities, contaminants, etc. induced in the discs during disc manufacturing.

5 With the continuing trend of providing ever increasing areal data storage densities on the disc recording surfaces, it is becoming increasingly difficult to produce discs with no media defects, and it is cost prohibitive to only use flawless discs and discard (scrap) discs containing such defects. Hence, disc drive manufacturers typically implement schemes to locate and map media defects so
10 that such locations are subsequently avoided in the writing of user data. During a formatting operation in which the data sectors are defined on the disc surfaces, the disc drive will map out sectors that coincide with the location of the detected media defects so that data are not written to defective sectors.

 At the same time, as areal data storage densities increase, the amount of
15 time required to scan the disc recording surfaces for defects increases; not only in terms of the additional amounts of data that must be written and read back from the disc surfaces, but also in terms of the time required to process the test results and generate a defect list. There is a need, therefore, for improvements in the art whereby media certification can be performed in a disc drive data handling system
20 in an efficient and reliable manner.

Summary of the Invention

 In accordance with preferred embodiments, a data handling system (disc drive) is provided in communication with a host device and includes a magnetic
25 medium having a number of user data wedges each disposed between an adjacent pair of servo data wedges. The servo data wedges store servo control data and the user data wedges are configured to store user data in data sectors. Each user data wedge has a unique address in relation to angular position of the user data wedge on the magnetic medium.

30 Defects in the magnetic medium are identified by writing a predetermined sequence of data (such as a 2T oscillating pattern) to the user data wedges. The data are subsequently read from the user data wedges to generate a readback

signal. A sequence of discrete time sample values are generated from the readback signal.

A defect in the magnetic medium is detected in relation to the magnitudes of the discrete time sample values. Upon detection of a media defect, a multi-bit information record is output to a buffer, the information record having at least one
 5 bit composing the address of the user data wedge containing the defect. A second multi-bit information record having at least one bit composing an address of the defect within the user data wedge containing the defect is also output to the buffer. Preferably, no information is output to the buffer when no defects are detected.

10 The information records are used to generate a defect list which is then used during a formatting operation in which user available data sectors are defined on the magnetic medium. In this way, defective sectors at locations of known defects are removed from use.

Since information records are preferably only placed in the buffer when
 15 media defects are detected, the time required to analyze the data records to identify the presence and location of defects is significantly reduced as compared to the prior art. Also, since the information records include embedded information as to the numeric address of the user data wedges containing defects, there is no need to search a large number of data records and count down to identify the particular
 20 data wedge (from index) containing each defect. Further, since the writing and reading of the data sequence do not require latency time to wait for the index point on the medium to first reach the head, significant time savings are achieved during the duration of the media certification operation.

These and various other features and advantages which characterize the
 25 claimed invention will be apparent from a reading of the following detailed description and a review of the associated drawings.

Brief Description of the Drawings

FIG. 1 is a top plan view of a disc drive data handling system constructed
 30 in accordance with preferred embodiments of the present invention.

FIG. 2 generally illustrates the manner in which servo data and user data are arranged on each of the disc surfaces of the disc drive of FIG. 1.

FIG. 3 illustrates the general format of each track defined on the disc surfaces.

FIG. 4 is functional block diagram of relevant portions of the disc drive of FIG. 1.

5 FIG. 5 is a graphical representation of a 2T signal written to a selected track and a resulting readback sinusoidal signal when a media defect occurs.

FIG. 6 is a flow chart for a DISC DRIVE ASSEMBLY routine generally illustrating the manner in which the disc drive of FIG. 1 is assembled and tested during disc drive manufacturing operations.

10 FIG. 7 is a flow chart for a MEDIA CERTIFICATION routine illustrating steps carried out in accordance with preferred embodiments of the present invention to check the disc recording surfaces for media defects.

FIG. 8 is a flow chart for a BUFFER RECORD ANALYSIS routine illustrating steps carried out during the routine of FIG. 7.

15

Detailed Description

FIG. 1 provides a top plan view of a disc drive data handling system 100 ("disc drive") constructed in accordance with preferred embodiments of the present invention. A base deck 102 and a top cover 104 (shown in partial cutaway) cooperate to form a sealed housing for the disc drive 100. A spindle motor 106 rotates a number of magnetic recording discs 108 at a constant, high speed.

20

An actuator assembly 110 supports an array of read/write heads 112 adjacent the respective disc surfaces. The actuator assembly 110 is rotated through the application of current to an actuator coil 114 of a voice coil motor (VCM) 116.

25 User data are stored by the heads 112 in fixed size data blocks (sectors) on concentric tracks defined on each of the disc surfaces.

FIGS. 2 and 3 generally illustrate the manner in which data are arranged on each of the recording surfaces of the discs 108. Servo data wedges 118 are written during disc drive manufacturing and radially extend across the recording surfaces like spokes on a wheel. Each servo wedge 118 is formed from a number of servo data fields 120 (FIG. 3), with one set of servo data fields 120 for each track 122.

30 The servo data are used to detect and control the position of the heads 112. The

number of servo data fields 120 per track varies depending upon the configuration of the drive, but a typical number is from about 100 to 300 servo data fields 120 on each track 122.

- 5 ~~118~~ Data wedges 124 are provided between each adjacent pair of servo wedges 118. User data fields 126 (sectors) are subsequently defined in the data wedges 124 and are used to store user data in fixed size data blocks, such as 512 bytes.

10 The general format of each servo data field 120 and user data field 126 is shown in FIG. 3. Each servo data field 120 includes an automatic gain control (AGC) field 128, a synchronization field 130, an index field 132, a Gray code (track address) field 134, and a position (POS) field 136. The AGC field 128 provides an oscillating preamble signal (such as a 2T pattern) to prepare servo control circuitry for receipt of the remaining servo data. The synchronization field 130 signals the presence of a servo data field 120 by storing a unique synchronization pattern that is a selected Hamming distance away from other possible combinations of bit patterns on the disc. The index field 132 indicates angular position of the servo data field 120 on the disc 108 with respect to an index point (i.e., zero rotational degrees). The Gray code field 134 provides a radial track address for the track 122, and the position field 136 enables the servo control circuitry to detect intra-track location of the head 112.

20 The user data fields 126 labeled D0, D1 and D2 are contiguous data fields and each include an AGC field 138, a synchronization field 140, a user data field 142 (in which 512 bytes of user data are stored), an error correction code (ECC) field 144 in which error detection and correction codes are stored, a pad field 146 and an intersector gap 148.

25 The user data field D3 is a non-contiguous, or split-sector data field 126 since a servo data field 120 splits the data field D3 into two parts. The use of split-sectors increases the available data storage of the disc drive. The first portion of the user data field D3 in FIG. 3 has a user data field 142 that stores 480 bytes of user data, and the second portion has a user data field 142 that stores the remaining 30 32 bytes of user data. Of course, other split-sectors on the disc 108 may have a different distribution of the user data bytes between the two halves depending upon the width of the data wedge 124.

FIG. 4 provides a functional block diagram of relevant circuitry of the disc drive 100 including an interface circuit 150, processor 152 and read/write channel 154. The interface circuit 150 communicates with a host device in accordance with an industry standard protocol, such as Small Computer Systems Interface (SCSI). The processor 152 provides top level control of the disc drive 100. The read/write channel 154 operates to write data to the discs 108 and to recover previously written data from the discs 108. For reference, the read channel portion of the read/write channel 154 is contemplated to use partial response, maximum likelihood (PRML) detection, although such is not limiting to the scope of the claimed invention.

During a normal data write operation, the host provides a write command to a host interface circuit 156 of the interface circuit 150 and loads the data to be written to a data buffer 158. The data are encoded by an encoder circuit 160 to provide run length limited (RLL) and error correction encoding, and the encoded data are serialized by a serializer 162. The output of the serializer 162 constitutes a non-return to zero (NRZ) signal used by a preamplifier/driver circuit 164 (preamp) to apply bi-directional write currents to the selected head 112 to write the data as a sequence of magnetic flux transitions on the disc recording surface.

During a subsequent data read operation, the data are transduced from the disc surface by the head 112 to provide a readback signal that is preamplified by the preamp 164, normalized by an AGC circuit 166 and filtered by an adaptive filter 168. The filtered signal undergoes time-domain filtering to a selected class of partial response waveforms (e.g., EPR4) by a finite response filter (FIR) 170. A sequence (Viterbi) detector 172 samples the output of the FIR 170 to provide a sequence of data values representative of the encoded data written to the disc 108.

A decoder 174 removes the RLL encoding and applies on-the-fly error detection and correction to provide the recovered user data to the buffer 158 for subsequent transfer to the host device. A sequencer 176 asserts read and write gate signals to control the writing and reading of data by the read/write channel 154.

The interface circuit 150 further comprises a data generator 178 which generates a 2T oscillating pattern for use at selected times including during a media certification operation during disc drive assembly operations. During media

certification, the 2T pattern is written across the entire width of each data wedge 124 on each disc surface. FIG. 5 provides a graphical representation of a 2T pattern waveform 180 (in NRZ format) and a corresponding readback signal 182, both plotted against an elapsed time x-axis 184 and an amplitude y-axis 186.

- 5 Under normal conditions, the 2T pattern will provide well behaved readback signal characteristics, as shown. However, the presence of a media defect, such as indicated at point 188, will provide a corresponding shift in the sample magnitude values of the readback signal. Such defects can be detected in relation to the sampled data values obtained during readback.

- 10 FIG. 6 provides a DISC DRIVE ASSEMBLY routine 200 illustrative of steps carried out in accordance with preferred embodiments to assemble and test the disc drive 100, including the aforementioned media certification. The disc drive 100 is initially assembled at step 202. The servo data in the servo data wedges 118 (FIG. 2) are written to the disc surfaces at step 204 during a servo track writing operation.

- 15 The routine proceeds with a media certification operation at step 206 to identify locations on the disc surfaces having media defects. A defect list is generated at step 208 from the results of the media certification operation, and this defect list is used during a formatting operation at step 210 in which the user data fields 126 are formed. The defect list enables the drive to avoid making user data fields 126 available for use at locations corresponding to the detected defects. Once the drive is formatted, the routine continues to step 212 for remaining processing including parametric configuration and extended temperature cycling testing. At the conclusion of such processing, the drive is ready for shipment and
- 20 the routine ends at step 214.

- 25 The media certification of step 206 of FIG. 6 is set forth in greater detail by the flow of FIG. 7. At step 216, a seek is performed to move the first selected head to the first user data track 122. Once the head is over the first user data track, a 2T pattern is written to each of the data wedges 124 of the track at step 218 using the data generator 178. It will be noted that the writing of the 2T pattern begins at any of the data wedges 124 on the track 122 and does not require latency time to wait for the first data wedge after the index point to reach the head 112. It will be noted

that other patterns besides a 2T pattern, such as a direct current (DC) erase signal, can readily be used as desired.

After the 2T pattern data have been written to each of the data wedges 118 on the track 122, the 2T pattern data are subsequently read at step 220. The reading preferably commences immediately upon completion of the writing of the data at step 218, so that the reading step can also begin at any data wedge 124 on the disc 108 without the need to wait for the index point to reach the head 112. This is in contrast to the prior art which typically requires waiting for the index point to be reached before certification data are written and read.

The time savings achieved from the present approach can be significant. For example, if the spindle motor 106 rotates the discs at 7,200 revolutions per minute, a full latency period (one revolution) will consume 8.33 milliseconds (8.33×10^{-3} seconds). For a two disc, four surface drive with 50,000 tracks per surface, and assuming each new track would require half a latency period (on average) before commencing writing and reading of data if the index point had to be identified first, the routine of FIG. 7 would eliminate about 14 minutes of test time per drive as compared to the prior art. This savings can be significant in a high volume manufacturing environment where a very large number of nominally identical drives are manufactured each day.

Continuing with step 220 of FIG. 7, a media scan controller circuit 222 ("controller") in the interface circuit 150 (FIG. 4) monitors the output of the sequence detector 172 for defects, such as shown at 188 in FIG. 5, through the application of appropriate thresholds to the sample values output from the sequence detector 172. The controller 222 uses a byte counter (not separately shown) to track position from the most recent servo sync pattern (field 130, FIG. 3) and writes defect data records to the buffer 158 in response to the detection of defects. Each data record is preferably a 16 bit value having the format shown in Table 1 (LSB, MSB):

Bit: 7 6 5 4 3 2 1 0 | 15 14 13 12 11 10 9 8

Table 1.

The following is an explanation of the informational content of these bits. When set, bit 15 is a header bit indicating that a new data wedge 124 contains at least one media defect. The wedges are numbered from the index point (indicated by index field 132, FIG. 3). For example, if there are a total of 288 servo wedges 118 and data wedges 124 on each disc surface, the data wedges 124 will be consecutively numbered 0 to 287 from the index point. Thus, if bit 15 is set, bits 9:0 (9 to 0) identify the particular wedge number in error. Bits 14:10 are not relevant (i.e., "don't care" bits) and no reference is made to these bits in interpreting the data record.

When bit 14 of the data record is set (and bit 15 is not set), then bits 12:0 of the data record indicate the location (byte) of a media defect within the data wedge 124 (counting from the first byte location of the data wedge). When bit 13 is set (and bit 15 is not set), then bits 12:0 of the data record minus one is the location (byte) of a media defect within the data wedge.

Some example data records will help illustrate the above format. Assume the first data record placed into the buffer during step 220 has a value of 79D8_H. This value corresponds to the binary sequence {0111 1001 1101 1000}. Bit 15 is set=1, and bits 9:0 have the value {00 0111 1001} = 121₁₀. Thus, the data record 79D8_H indicates that data wedge=121 contains at least one media defect.

Assume the next data record has a value 3661_H. This corresponds to the binary sequence {0011 0110 0110 0001}. Bit 15=0, bit 14=1 and bit 13=1. Bits 12:0 have the value {0 0001 0011 0110}=310₁₀. Thus, Bytes 309 and 310 in the 121st data wedge have detected media defects.

Finally, assume the next data record in the sequence has a value ED42_H. This corresponds to the binary sequence {1110 1101 0100 0010}. Bit 15 is set=0, bit 14 is set=1, and bit 13 is set=0. Bits 12:0 have the value {0 0010 1110 1101}=749₁₀. This means that the 749th byte in the 121st data wedge has a detected media defect.

The operation of step 220 in FIG. 7 will thus continue until all of the data wedges 124 of the selected track are read. Decision step 224 inquires whether any buffer records were provided to the buffer 158 by the controller 222; if not, the

disc drive 100 seeks to the next user track at step 226. Decision step 228 inquires whether all user tracks have been evaluated. If so, the process is complete and the routine returns to the flow of FIG. 6 at step 230; if not, the routine returns back to step 218 for evaluation of the new user track.

5 When buffer records are present in the buffer, however, the flow of FIG. 7 continues to a buffer record analysis routine 232, as set forth more fully by FIG. 8. The buffer record analysis routine proceeds to scan the first record in the buffer 158 at step 234. Decision step 236 inquires whether bit 15 is set (i.e., bit 15=1); if so, the flow proceeds to step 238 and the data wedge number is identified by bits 10 (9:0) in the data record. The flow passes to decision step 240 which inquires whether the end of the list of records in the buffer has been reached. If not, the routine passes to step 242 wherein the next record is scanned and the flow returns to step 236.

 When bit 15 is not set, the flow passes from decision step 236 to step 244 15 which determines whether bit 14 and/or bit 13 are set. If so, the locations of the defective bytes are determined from bits (12:0) in the data record at step 246. It will be recalled that bits (12:0) identify a defective byte when bit 14 is set, and bits (12:0)-1 identify a defective byte when bit 13 is set. The corresponding defective sector(s) that line up with the defective bytes are next identified at step 248. This 20 can be accomplished through the use of a sector map indicating what portions of the various data wedges 122 correspond to which sectors 126.

 The flow of FIG. 8 continues until all of the data records in the buffer 158 have been evaluated, after which the routine returns to the flow of FIG. 7 at step 248.

25 It will be noted that data records are placed into the buffer 158 only when media defects are detected, unlike prior art techniques that place a header record into the buffer for each data wedge 124 regardless whether defects are present in each wedge. This significantly reduces the number of data records that require analysis to identify the presence of detected media defects. A related advantage is 30 the embedding of the particular data wedge number in the header records (i.e., the records in which bit 15=1); this eliminates the need to search a large number of data records and count down to identify the particular data wedge (from index)

containing each defect. It is contemplated that the analysis of FIG. 8 requires significantly fewer processing resources to complete and thus provides substantial time savings over prior art defect management techniques.

It will now be understood that the present invention (as embodied herein
5 and as claimed below) is directed to an apparatus and method for detecting defects in a magnetic medium of a data handling system.

In accordance with preferred embodiments, a disc drive (such as 100)
includes a magnetic medium (such as 108) having a number of user data wedges
(such as 124) each disposed between an adjacent pair of servo data wedges (such
10 as 118). The servo data wedges store servo control data and the user data wedges
are configured to store user data in data sectors (such as 126). Each user data
wedge has a unique address in relation to angular position of the user data wedge
on the magnetic medium.

Defects in the magnetic medium are identified by writing a predetermined
15 sequence of data to the user data wedges (such as by step 218). The data are
subsequently read from the user data wedges to generate a readback signal (such as
by step 220). A sequence of discrete time sample values are generated from the
readback signal (such as by 172). A defect in the magnetic medium is detected in
relation to the magnitudes of the discrete time sample values. A multi-bit
20 information record is output to a buffer (such as 158), the information record
having at least one bit composing the address of the user data wedge containing the
defect. Preferably, a second multi-bit information record having at least one bit
composing an address of the defect within the user data wedge containing the
defect is also output to the buffer, and no information is output to the buffer when
25 no defects are detected.

The predetermined sequence of data preferably comprises a 2T oscillating
pattern. Further, a selected servo data wedge corresponds to an index point as an
angular reference for the magnetic medium, a selected servo data wedge
immediately precedes a first user data wedge, and the reading of the data
30 commences at a selected data wedge other than the first user data wedge on the
magnetic medium.

The method further preferably includes a step of formatting the data handling system to form a plurality of user available data sectors in the user data wedges for subsequent use in storing user data, wherein a user available data sector is not formed over a defect (such as by step 210).

5 In accordance with other preferred embodiments, a data handling system (such as 100) comprises a magnetic medium (such as 108) having a number of user data wedges (such as 124) each disposed between an adjacent pair of servo data wedges (such as 118), the servo data wedges storing servo control data and the user data wedges configured to store user data in data sectors (such as 126). Each
10 user data wedge having a unique address in relation to angular position of the user data wedge on the magnetic medium.

The data handling system further comprises a head (such as 112) which writes a predetermined sequence of data to the user data wedges and subsequently reads the data from the user data wedges to generate a readback signal; a read
15 channel (such as 154) which generates a sequence of discrete time sample values from the readback signal; a data buffer (such as 158) configured to temporarily store data during transfer between the magnetic medium and a host device; and a media scan controller (such as 222) which identifies a defect in the magnetic medium in relation to the discrete time sample values and outputs to the data
20 buffer a multi-bit information record having at least one bit composing the address of the user data wedge containing the defect.

For purposes of the following claims, the function of the recited "first means" will be understood as being carried out by the disclosed media scan controller 222 of the interface circuit 150, which operates in accordance with the
25 steps of FIGS. 6-8.

It is to be understood that even though numerous characteristics and advantages of various embodiments of the present invention have been set forth in the foregoing description, together with details of the structure and function thereof, this detailed description is illustrative only, and changes may be made in
30 detail, especially in matters of structure and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed. For example,

the particular elements may vary depending on the particular application for the media certification routine while maintaining the same functionality without departing from the spirit and scope of the invention.

- In addition, although the embodiments described herein are generally
- 5 directed to a media certification routine for a disc drive, it will be appreciated by those skilled in the art that the routine can be used for other types of data handling systems, such as optical disc systems, without departing from the spirit and scope of the claimed invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216